



L6 ANSWER 46 OF 52 CA COPYRIGHT 2005 ACS on STN
AN 92:219932 CA
ED Entered STN: 12 May 1984
TI **Cement** setting retardant
IN Shinoda, Katsuro; Tamaki, Norio
PA Sekisui Chemical Co. Ltd., Japan
SO Jpn. Kokai Tokkyo Koho, 4 pp.
CODEN: JKXXAF

DT Patent
LA Japanese
IC C04B013-24; C04B013-20
CC 58-1 (Cement and Concrete Products)
FAN. CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 54159443	A2	19791217	JP 1978-69055	19780607
PRAI	JP 1978-69055	A	19780607		

CLASS

PATENT NO.	CLASS	PATENT FAMILY CLASSIFICATION CODES
------------	-------	------------------------------------

JP 54159443	IC	C04B013-24IC C04B013-20
-------------	----	-------------------------

AB A mixture containing water-soluble poly(acrylic acid), poly(methacrylic acid), or its salt and polyethylene glycol or polyvinylpyrrolidone is used as a **cement** setting retardant. Thus, rapid setting **cement** (initial setting time 30 s) containing aluminous **cement** 100 and Ca(OH)₂ 20 parts was mixed with 0.05 part a 65:35 poly(acrylic acid) [9003-01-4]-polyethylene glycol [25322-68-3] mixture and suitable amount of water, and shaped. Its initial setting time was 35 min.

ST polyacrylic acid **cement** setting retardant; polyethylene glycol **cement** setting retardant

IT **Cement**
(setting **retarders** for, from poly(acrylic acid) mixture with polyethylene glycol)

IT 25322-68-3